

- Tear drop shaped jaws for ease of use in tight places and crowded cable areas.
- Designed to meet internationally proven safety standards such as IEC61010-1, UL3111 and VDE0411.
- Three functions in one unit; AC current, AC voltage and resistance.
- Resistance range provides audible continuity test.
- Frequency response from 40Hz to 1kHz on AC current and voltage ranges.



AC A	200/600A  ±1.5%rdg±4dgt [50/60Hz] (200A)  ±1%rdg±3dgt [50/60Hz] (600A)  ±2%rdg±5dgt [45Hz~1kHz]
AC V	200/600V  ±1%rdg±2dgt [50/60Hz]  ±1.5%rdg±4dgt [45Hz~1kHz]
Ω	200Ω  ±1.2%rdg±2dgt
Continuity buzzer	buzzer sounds below 30±20Ω
Conductor Size	Ø33mm max.
Safety Standard	IEC61010-1 CAT.III 600V Pollution Degree 2 IEC61010-2-031
Frequency Response	45Hz~1kHz
Withstand Voltage	550V AC for 1 minute
Power Source	6F22(9V) × 1
Dimensions	208(L) × 91(W) × 40(D)mm
Weight	400g approx.
Accessories	7066(Test Leads) 9079(Carrying Case) 6F22 × 1 Instruction Manual
Optional	8004/8008 (Multi-Tran) 8021(Energizer)