

## MANOMETER

MTP ST-8890

### DIGITAL MANOMETER

*New*



- Simple fittings for hose connection
- Digital display of gauge or differential pressure from 0 to  $\pm 2\text{psi}$  or 0 to  $\pm 5\text{psi}$
- Over range and low battery indicator
- Auto power off preserves remaining battery life
- It features 11 selectable units of measure
- MIN/MAX and data hold function

FUNCTION	RANGE	RESOLUTION	FUNCTION	RANGE	RESOLUTION
inH <sub>2</sub> O	138.3	0.1	ozin <sup>2</sup>	80.00	0.01
psi	5.000	0.001	ftH <sub>2</sub> O	11.53	0.01
mbar	344.7	0.1	cmH <sub>2</sub> O	351.5	0.1
kPa	34.47	0.01	kgcm <sup>2</sup>	0.351	0.001
inHg	1.018	0.001	bar	0.344	0.001
mmHg	258.5	0.1			

CE

INCLUDED ACCESSORIES: carrying case, software

## HEAT STRESS MONITOR

TES 1369

### HEAT STRESS MONITOR

*New*



- WBGTin, WBGTout and dew point
- Calculates relative humidity, heat index and humidex
- Globe, dry bulb and wet bulb temperature
- Datalogging area thermal environment monitor
- Maximum / minimum recording reading
- Datalogging capacity of 15000 sets (manual 99 sets)
- Data hold function

FUNCTION	
Measurements	Globe, dry bulb, wet bulb temperature
Measurement computed	WBGTin, WBGTout, relative humidity, heat index, humidex, dew point
Temperature measurement	Sensor: NTC, thermistor Range: -5°C to + 60°C (23°F to 140°F) Resolution: 0.1°C / 0.1°F Accuracy: $\pm 0.5^\circ\text{C} / \pm 0.9^\circ\text{F}$
Memory capacity	Manual: 99 sets Auto: 15000 sets

CE

INCLUDED ACCESSORIES: 9V battery, RS-232 cable, software, AC adaptor, 10 meters sensor cable, 2 inch diameter globe, 6 inch diameter globe, carrying case